

# ArrowSelect™ Series



## Features and Benefits

- **Quick delivery:** By maintaining standard components.
- **Optimum quality:** Finished components manufactured to exact tolerances and inspected to ensure immediate response to customer's needs.
- **Maximum value:** Manufactured along with our other product lines offers a large purchasing volume and efficiencies of scale to provide savings that can be passed on to you.
- Heavy-duty stainless steel or painted mild steel construction.
- Full array of complimentary accessories - guide rails, brackets (adjustable only), supports (pedestal and angle "H" style) and transfer aids (roller dead plates, stainless steel dead plates and side transfer plates), drive end, idle end and incline/decline modules.

	Standard Features	Optional Features
<b>Frame Construction</b>	Open Top	N/A
<b>Frame Material</b>	Hot rolled mild steel, paint steel-it grey color match	Stainless steel with #4 polish
<b>Standard Modules</b>	Idle ends, drive ends, 30, 45 & 90 degree curves, parallel transfers, incline/decline modules	N/A
<b>Chain Return</b>	Roller	Serpentine
<b>Intermediate Frame Depth</b>	5 1/2"	6 1/2"
<b>Drive, Idle and Transfer Frame Depth</b>	8" with end caps	N/A
<b>Wearstrips</b>	UHMW Clip-on	N/A
<b>Bearings</b>	2 hole flange mounted	N/A
<b>Guide Rail Brackets</b>	Adjustable slotted steel L-brackets	N/A
<b>Guide Rails</b>	Arrowglide aluminum with round or flat profile	Stainless steel channel with round or flat UHMW insert
<b>Drive Mount</b>	Adjustable below mount, LH or RH	None
<b>Power Transmission</b>	#50 roller chain with ABS plastic chain guard	Stainless steel chain guard
<b>Speeds</b>	Fixed at 30 to 200 fpm	
<b>Standard Lengths</b>	1'-0", 2'-0" & 3'-0" idle ends, 3'-0" drive ends, 4'-0" parallel transfers. All curves have 6" tangents. Curve radius - 24" for all except 3 1/4" chain conveyor (18" radius)	Intermediate sections available in 1/2" increments from 6" to 10'-0"
<b>Supports</b>	1/4" x 1 1/2" x 1 1/2" Mild steel angle with welded cross member and plated, mild steel adjustable foot	Stainless steel angle with formed SS foot, pedestal supports with yoke
<b>Height Range</b>	27" - 57" +/- 3"	Custom heights available in 1" increments
<b>Shafts</b>	1" dia steel (cold rolled or Type 303 stainless) with 1/4" keyway	N/A
<b>Tabletop Chain Widths</b>	3 1/4", 4 1/2", 7 1/2" 10", 12", dual 7 1/2"	N/A
<b>Chain Types</b>	Straight running	Side flexing
<b>Chain Material</b>	LF plastic	Mild steel, stainless steel
<b>Other Options</b>		Roller deadplates, stainless steel deadplates, 3/4" side transfer deadplates, flushmount areas on intermediate sections